

Overview

Aruba 2930F Switch Series

The Aruba 2930F Switch Series is designed for customers creating smart digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These convenient Layer 3 network switches include built-in uplinks and PoE power, and are simple to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager, Aruba AirWave and cloud-based Aruba Central.

A powerful Aruba ProVision ASIC delivers performance, robust feature support and value with programmability for the latest applications. Stacking with Virtual Switching Framework (VSF) provides simplicity and scalability. The 2930F supports built-in 1GbE or 10GbE uplinks, PoE+, Access OSPF routing, Dynamic Segmentation, robust QoS, RIP routing, and IPv6 with no software licensing required.

The Aruba 2930F Switch Series provides a convenient and cost-effective access switch solution that can be quickly set up with Zero Touch Provisioning. The robust basic Layer 3 feature set includes a limited lifetime warranty.



Aruba 2930F Switch Series

Key Features

- Aruba Layer 3 switch series with VSF stacking, static, RIP and Access OSPF Routing, dynamic segmentation, ACLs, and robust QoS
- Supports cloud and on-premises management. And advanced policy management using Aruba ClearPass
- Convenient built-in 1GbE or 10GbE uplinks and up to 740 W PoE+
- Software-defined ready with REST APIs and OpenFlow support
- Simple deployment with Zero Touch Provisioning

Standard Features

Enhanced Capabilities

Unified Wired and Wireless Support

- **Supports unified wired and wireless policies**
Aruba ClearPass Policy Manager
- **Switch auto-configuration**
automatically configures switch for different settings such as VLAN, CoS, PoE max power, and PoE priority when an Aruba access point is detected.
- **User role**
defines a set of switch-based policies in areas such as security, authentication, and QoS. A user role can be assigned to a group of users or devices, using switch-based local user role or download from ClearPass
- **Aruba Dynamic Segmentation**
automatically enforces user, device and application-aware policies on Aruba wired and wireless networks. Automated device profiling, role-based access control, and Layer 7 firewall features deliver enhanced visibility and performance for a better overall experience for both IT and end users alike.
- **Dynamic segmentation**
provides a secured tunnel to transport network traffic on a per-port or per-user-role basis to an Aruba Controller. In per-user-role Tunneled Node, users are authenticated with ClearPass Policy Manager which can direct the traffic to be tunneled to Aruba controller or switch locally
- **Static IP visibility**
allows ClearPass to do accounting for clients with static IP address

Software-defined networks

- **REST APIs and OpenFlow**
Supports multiple programmatic interfaces, including REST APIs and Openflow 1.0 and 1.3, to enable automation of network operations, monitoring, and troubleshooting.

Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p)**
for classification into eight priority levels mapped to eight queues
- **Layer 4 prioritization**
based on TCP/UDP port numbers
- **Class of Service (CoS)**
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Rate limiting**
sets per-port ingress enforced maximums and per-port, per-queue minimums
- **Large buffers**
provide graceful congestion management
- **Unknown Unicast Rate Limiting**
throttles unicast packets with unknown destination addresses and limits flooding on the VLAN

Connectivity

- **Convenient built-in 10 Gbps Ethernet (4 x SFP+) uplinks**
available on select models
- **Auto-MDIX**
provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **12-port fanless model available**
12x 1Gbps Ethernet PoE+ ports and four built-in uplinks (2x SFP+ and 2x 1GBASE-T). Built-in power supply.
- **IEEE 802.3at Power over Ethernet (PoE+)**
provides up to 30 W per port that allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; eliminates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments
- **Support for pre-standard PoE** detects and provides power to pre-standard PoE devices



Standard Features

IPv6

- **IPv6 host** enables switches to be managed in an IPv6 network
- **Dual stack (IPv4 and IPv6)**
 - transitions from IPv4 to IPv6, supporting connectivity for both protocols
- **MLD snooping**
 - forwards IPv6 multicast traffic to the appropriate interface
- **IPv6 ACL/QoS**
 - supports ACL and QoS for IPv6 network traffic
- **IPv6 routing**
 - supports static and RIPng protocols
- **Security**
 - provides RA guard, DHCPv6 protection, dynamic IPv6 lockdown, and ND snooping

Performance and efficiency

- **Energy-efficient design**
 - **80 PLUS Silver Certified power supply**
increases power efficiency and savings
 - **Energy-efficient Ethernet (EEE) support**
reduces power consumption in accordance with IEEE 802.3az
- **Designed with the latest Aruba Provision ASIC**
providing very low latency, increased packet buffering, and adaptive power consumption
- **Selectable queue configurations**
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- **-Stacking topology**
 - Virtual Switching Framework (VSF) front plane stacking creates one virtual resilient switch from up to eight switches.
Notes: Requires ArubaOS-Switch 16.06 software.
 - Ring topology supports up to an 8-member stack
 - Virtualized switching provides simplified management as the switches act as a single chassis when stacked

Convergence

- **IP multicast snooping and data-driven IGMP**
automatically prevent flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**
defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to configure automatically network devices such as IP phones
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
facilitates easy mapping using network management applications with LLDP automated device discovery protocol
- **PoE and PoE+ allocations**
support multiple methods (automatic, IEEE 802.3at dynamic, LLDP-MED fine grain, IEEE 802.3af device class, or user-specified) to allocate and manage PoE/PoE+ power for more efficient energy savings
- **Local MAC Authentication**
assigns attributes such as VLAN and QoS using a locally configured profile that can be a list of MAC prefixes
- **IP multicast routing**
includes PIM Sparse and Dense modes to route IP multicast traffic (limited to 16 interfaces)
- **Protocol Independent Multicast for IPv6**
supports one-to-many and many-to-many media casting use cases such as IPTV over IPv6 networks

Monitor and diagnostics

- **Digital optical monitoring of SFP+ and 1000BASE-T transceivers**
allows detailed monitoring of the transceiver settings and parameters



Standard Features

Resiliency and high availability

- **IEEE 802.1s Multiple Spanning Tree**
provides high link availability by allowing multiple spanning trees; provides legacy support for IEEE 802.1d and IEEE 802.1w
- **Virtual Router Redundancy Protocol (VRRP)**
allows groups of two routers to dynamically back each other up to create highly available routed environments for IPv4 and IPv6 networks (limited to 128 VRs)
- **IEEE 802.3ad link-aggregation-control protocol (LACP) and port trunking**
support up to 60 static or dynamic trunks with each trunk having up to eight links (ports) per static trunk
- **SmartLink**
provides easy-to-configure link redundancy of active and standby links
- **SNMPv1, v2, and v3**
provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption

Simplified configuration and management

- **Aruba Central support**
cloud based management platform offers simple, secure, and cost effective way to manage switches
- **Zero-Touch Provisioning (ZTP)**
simplifies installation of the switch infrastructure using Aruba Activate or a DHCP-based process with AirWave and Central Network Management
- **Built-in programmable and easy-to-use REST API interface**
provides configuration automation for campus networks
- **Flexible management with same hardware**
supports both cloud-based Central and on-premises AirWave with the same hardware, ensuring management platform changes without ripping and replacing switching infrastructure

Manageability

- **Dual flash images**
provides independent primary and secondary operating system files for backup while upgrading
- **Friendly port names**
allow assignment of descriptive names to ports
- **Find-Fix-Inform feature**
finds and fixes common network problems automatically, then informs administrator
- **Supports multiple configuration files**
stored to a flash image
- **RMON, XRMON, and sFlow**
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Troubleshooting**
ingress and egress port monitoring enable more efficient network problem solving
- **Unidirectional link detection (UDLD)**
monitors the link between two switches and blocks the ports on both ends of the link if the link goes down at any point between the two devices
- **IP service level agreements (SLA) for voice**
monitor quality of voice traffic using the UDP jitter and UDP jitter for VoIP tests

Software releases

- to find software for your product, refer to <http://www.hpe.com/networking/support>; for details on the software releases available with your product purchase, refer to <http://www.hpe.com/networking/warrantysummary>

Layer 3 services

- **DHCP server**
centralizes and reduces the cost of IPv4 address management



Standard Features

Layer 2 switching

- **IEEE 802.1ad Q-in-Q**
increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network
- **VLAN Support and Tagging**
supports IEEE 802.1Q (4094 VLAN IDs) and 2K VLANs simultaneously
- **Jumbo packet support**
improves the performance of large data transfers; supports frame size of up to 9220 bytes
- **IEEE 802.1v protocol VLANs**
isolate select non-IPv4 protocols automatically into their own VLANs
- **Rapid Per-VLAN Spanning Tree (RPVST+)**
allows each VLAN to build a separate spanning tree to improve link bandwidth usage; is compatible with PVST+
- **GVRP and MVRP**
allows automatic learning and dynamic assignment of VLANs
- **VxLAN**
encapsulation (tunneling) protocol for overlay network that enables a more scalable virtual network deployment

Layer 3 routing

- **Static IP routing**
provides manually configured routing; includes ECMP capability
- **256 static and 10,000 RIP routes**
facilitate segregation of user data, without adding external hardware
- **Routing Information Protocol (RIP)**
provides RIPv1, RIPv2, and RIPv3 routing
- **Access OSPF**
provides OSPFv2 and OSPFv3 protocols for routing between access and the next layer on the LAN. Only one OSPF area and up to 8 interfaces are supported
- **Policy-based routing**
uses a classifier to select traffic that can be forwarded based on policy set by the network administrator (limited to 16 next-hop routes)

Customer first, customer last support

When your network is important to your business, then your business needs the backing of Aruba Support Services. Partner with Aruba product experts to increase your team productivity, keep pace with technology advances, software releases, and obtain break-fix support.

- Foundation Care for Aruba support services include priority access to Aruba Technical Assistance Center(TAC) engineers 24x7x365, flexible hardware and onsite support options, and total coverage for Aruba products. Aruba switches with assigned Aruba Central subscriptions benefit with option for additional hardware support only.
- Aruba Pro Care adds fast access to senior Aruba TAC engineers, who are assigned as a single point of contact for case management, reducing the time spent addressing and resolving issues.

For complete details on Foundation Care and Aruba Pro Care, please visit: <https://www.arubanetworks.com/supportservices/>

Warranty and support

- **Limited Lifetime Warranty**
see <http://www.hpe.com/networking/warrantysummary> for warranty and support information included with your product purchase.



Standard Features

Security

- **Control Plane Policing set rate limit on control protocols to protect CPU overload from DOS attacks**
- **Multiple user authentication methods**
 - uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server to authenticate in accordance with industry standards
 - supports Web-based authentication
 - supports MAC-based authentication
- **Authentication flexibility**
 - **Multiple IEEE 802.1X users per port**
provides authentication of multiple devices on a single port; prevents a user from "piggybacking" on another user's IEEE 802.1X authentication
 - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port**
switch port will accept up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **TPM-based Security**
includes a Trusted Platform Module (TPM) for secure hardware-based generation and storage of cryptographic keys that can be used for a variety of authentication purposes
- **Access control lists (ACLs)**
provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **Source-port filtering**
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**
eases switch management security administration by using a password authentication server
- **Secure shell**
encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **Radius over TLS (RadSec)**
allows users to use a more secure and reliable mode of communications between switch and radius servers over unsecure networks
- **MAC address lockout**
prevents particular configured MAC addresses from connecting to the network
- **Secure FTP**
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Switch management logon security**
helps secure switch CLI logon by optionally requiring either RADIUS or TACACS+ authentication
- **Custom banner**
displays security policy when users log in to the switch
- **STP BPDU port protection**
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **DHCP protection**
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection**
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **STP root guard**
protects the root bridge from malicious attacks or configuration mistakes
- **Identity-driven ACL**
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user

Standard Features

- **Per-port broadcast throttling**
Configures broadcast control selectively on heavy traffic port uplinks
 - **Private VLAN**
provides network security by restricting peer-to-peer communication to prevent a variety of malicious attacks; typically a switch port can only communicate with other ports in the same community and/or an uplink port, regardless of VLAN ID or destination MAC address
 - **Open authentication role**
simplifies first-time deployment of AAA in brownfield deployments by allowing full network access for failed clients and provides instant connectivity as soon as a client is plugged-in
 - **Critical authentication role**
ensures that important infrastructure devices such as IP phones are allowed network access even in the absence of a RADIUS server
 - **MAC pinning**
allows non-chatty legacy devices to stay authenticated by pinning client MAC addresses to the port until the clients logoff or get disconnected
 - **Enrollment over Secure Transport (EST)**
enhances the switch PKI infrastructure with a simpler, scalable and more secure method of certificate provisioning, re-enrollment and renewal
-



Configuration Information

BTO Models

Rule #	Description	SKU
1, 2, 3,10	Aruba 2930F 12G PoE+ 2G/2SFP+ Switch	JL693A
	<ul style="list-style-type: none"> 12 RJ-45 PoE+ autosensing 10/100/1000 ports 2 SFP/SFP+ 1G/10G ports min=0 \\ max=2 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 12G PoE+ 2G/2SFP+ Switch PDU	JL693A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 12G PoE+ 2G/2SFP+ Switch PDU	JL693A#B2C
1, 2, 3,10	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 12G PoE+ 2G/2SFP+ Switch 220v	JL693A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A) 	
	Aruba 2930F 12G PoE+ 2G/2SFP+ Switch No Loc	JL693A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3,10	Aruba 2930F 24G 4SFP+ Switch	JL253A
	<ul style="list-style-type: none"> 24 RJ-45 autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 24G 4SFP+ Switch PDU NA, JP or TW	JL253A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G 4SFP+ Switch PDU ROW	JL253A#B2C
1, 2, 3,10	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G 4SFP+ Switch United States 220 volt	JL253A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G 4SFP+ Switch	JL253A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3,10	Aruba 2930F 48G 4SFP+ Switch	JL254A
	<ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 24G 4SFP+ Swch PDU	JL254A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G 4SFP+ Swch PDU	JL254A#B2C
1, 2, 3,10	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G 4SFP+ Swch US220v	JL254A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G 4SFP+ Switch	JL254A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3,10	Aruba 2930F 24G PoE+ 4SFP+ Switch	JL255A
	<ul style="list-style-type: none"> 24 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	

Configuration Information

Rule #	Description	SKU
	Aruba 2930F 24G PoE+ 4SFP+ Switch PDU NA, JP or TW	JL255A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch PDU ROW	JL255A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch United States 220 volt	JL255A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch	JL255A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3,10	Aruba 2930F 48G PoE+ 4SFP+ Switch	JL256A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch PDU NA, JP or TW	JL256A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch PDU ROW	JL256A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch United States 220 volt	JL256A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch	JL256A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3,10	Aruba 2930F 8G PoE+ 2SFP+ Switch	JL258A
	<ul style="list-style-type: none"> 8 RJ-45 PoE+ autosensing 10/100/1000 ports 2 SFP/SFP+ 1G/10G ports min=0 \\ max=2 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 8G PoE+ 2SFP+ Switch PDU NA, JP or TW	JL258A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 8G PoE+ 2SFP+ Switch PDU ROW	JL258A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 8G PoE+ 2SFP+ Switch United States 220 volt	JL258A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 8G PoE+ 2SFP+ Switch	JL258A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 3,10	Aruba 2930F 24G 4SFP Switch	JL259A
	<ul style="list-style-type: none"> 24 RJ-45 autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 24G 4SFP Switch PDU NA, JP or TW	JL259A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G 4SFP Switch PDU ROW	JL259A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G 4SFP Switch United States 220 volt	JL259A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G 4SFP Switch	JL259A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	

Configuration Information

Rule #	Description	SKU
1, 3,10	Aruba 2930F 48G PoE+ 4SFP 740W Switch <ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	JL557A
	Aruba 2930F 48G PoE+ 4SFP 740W Switch PDU NA, JP or TW <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	JL557A#B2B
	Aruba 2930F 48G PoE+ 4SFP 740W Switch PDU ROW <ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	JL557A#B2C
	Aruba 2930F 48G PoE+ 4SFP 740W Switch United States 220 volt <ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	JL557A#B2E
	Aruba 2930F 48G PoE+ 4SFP 740W Switch <ul style="list-style-type: none"> No Localized Power Cord Selected 	JL557A#AC3
1, 3,10	Aruba 2930F 48G 4SFP Switch <ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	JL260A
	Aruba 2930F 48G 4SFP Switch PDU NA, JP or TW <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	JL260A#B2B
	Aruba 2930F 48G 4SFP Switch PDU ROW <ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	JL260A#B2C
	Aruba 2930F 48G 4SFP Switch United States 220 volt <ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	JL260A#B2E
	Aruba 2930F 48G 4SFP Switch <ul style="list-style-type: none"> No Localized Power Cord Selected 	JL260A#AC3
1, 3,10	Aruba 2930F 24G PoE+ 4SFP Switch <ul style="list-style-type: none"> 24 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	JL261A
	Aruba 2930F 24G PoE+ 4SFP Switch PDU NA, JP or TW <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	JL261A#B2B
	Aruba 2930F 24G PoE+ 4SFP Switch PDU ROW <ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	JL261A#B2C
	Aruba 2930F 24G PoE+ 4SFP Switch United States 220 volt <ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	JL261A#B2E
	Aruba 2930F 24G PoE+ 4SFP Switch <ul style="list-style-type: none"> No Localized Power Cord Selected 	JL261A#AC3
1, 3,10	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch <ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	JL558A
	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch PDU NA, JP or TW <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	JL558A#B2B

Configuration Information

1, 3,10	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch PDU ROW	JL558A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch United States 220 volt	JL558A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch	JL558A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
	Aruba 2930F 48G PoE+ 4SFP Switch	JL262A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP Switch PDU NA, JP or TW	JL262A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP Switch PDU ROW	JL262A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP Switch United States 220 volt	JL262A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP Switch	JL262A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	

TAA Compliant Chassis

Rule #	Description	SKU
1, 2, 3, 4, 8, 9,10	Aruba 2930F 8G PoE+ 2SFP+ TAA-compliant Switch	JL692A
	<ul style="list-style-type: none"> 8 RJ-45 PoE+ autosensing 10/100/1000 ports 2 SFP/SFP+ 1G/10G ports min=0 \\ max=2 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 8G PoE+ 2SFP+ TAA-compliant Switch PDU	JL692A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 8G PoE+ 2SFP+ TAA-compliant Switch PDU	JL692A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 8G PoE+ 2SFP+ TAA-compliant Switch 220v	JL692A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A) 	
	Aruba 2930F 8G PoE+ 2SFP+ TAA-compliant Switch No Loc	JL692A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3, 4, 8, 9,10	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch	JL263A
	<ul style="list-style-type: none"> 24 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch PDU NA, JP or TW	JL263A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch PDU ROW	JL263A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	

Configuration Information

Rule #	Description	SKU
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch United States 220 volt	JL263A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch	JL263A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3, 4, 8, 9,10	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch	JL559A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU NA, JP or TW	JL559A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU ROW	JL559A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch United States 220 volt	JL559A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch	JL559A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3, 4, 8, 9,10	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch	JL264A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch PDU NA, JP or TW	JL264A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch PDU ROW	JL264A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch United States 220 volt	JL264A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch	JL264A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
	Configuration Rules	
1	The following Transceivers install into this Switch:	
	Aruba 1G SFP LC SX 500m OM2 MMF Transceiver	J4858D
	Aruba 1G SFP LC LX 10km SMF Transceiver	J4859D
	Aruba 1G SFP LC LH 70km SMF Transceiver	J4860D
	Aruba 1G SFP RJ45 T 100m Cat5e Transceiver	J8177D
	Aruba 100M SFP LC FX 2km MMF Transceiver	J9054D
2	The following Transceivers install into this Switch:	
	Aruba 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
	Aruba 10G SFP+ LC LR 10km SMF Transceiver	J9151E
	Aruba 10G SFP+ LC ER 40km SMF Transceiver	J9153D
	Aruba 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
	Aruba 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D
3	Localization required on orders without #B2B, #B2C or #B2E options.	

Configuration Information

4	TAA Switch Chassis are available in the US, UK, Israel, Vietnam, South Korea, India and Taiwan only.	
8	The following Transceivers install into this Switch:	
	Aruba 1G SFP LC SX 500m MMF TAA Transceiver	JL745A
	Aruba 1G SFP LC LX 10km SMF TAA Transceiver	JL746A
	Aruba 1G SFP RJ45 T 100m Cat5e TAA Transceiver	JL747A
9	The following Transceivers install into this Switch:	
	Aruba 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
	Aruba 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
10	Unbuildable/FAN required, generates CFGU: If order is quoted for India and contains "#B2C" Option, then Display the following:	
	For BTO shipments to India:	
	Please replace <Base Model>#B2C option with <Base Model>#AC3 in the Bill of Materials and add the appropriate INDIA PDU Power Cord below via Ad-Hoc:	
	For Factory Integration of Power Cord, please add "#0D1" to the Power Cord Sku suffix. (Ex. JL671A#0D1)	
	HPE 2.0m C13 to C14 PDU India Power Cord	JL671A
	HPE 2.5m C15 to C14 PDU India Power Cord	JL672A
	HPE 2.5m C19 to C20 PDU India Power Cord	JL673A
Notes:	<ul style="list-style-type: none"> Drop down under power supply should offer the following options and results: Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO) Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO) #AC3 - No Power Cord 	

Rack Level Integration CTO Models

Rule #	Description	SKU
1, 2, 3, 4, 5,10	Aruba 2930F 24G 4SFP+ Switch	JL253A
	<ul style="list-style-type: none"> 24 RJ-45 autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 24G 4SFP+ Switch PDU NA, JP or TW	JL253A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G 4SFP+ Switch PDU ROW	JL253A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G 4SFP+ Switch United States 220 volt	JL253A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G 4SFP+ Switch	JL253A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3, 4, 5,10	Aruba 2930F 48G 4SFP+ Switch	JL254A
	<ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 24G 4SFP+ Swch PDU	JL254A#B2B

Configuration Information

1, 2, 3, 4, 5,10	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G 4SFP+ Swch PDU	JL254A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G 4SFP+ Swch US220v	JL254A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G 4SFP+ Switch	JL254A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch	JL255A
	<ul style="list-style-type: none"> 24 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
Rule #	Description	SKU
1, 2, 3, 4, 5,10	Aruba 2930F 24G PoE+ 4SFP+ Switch PDU NA, JP or TW	JL255A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch PDU ROW	JL255A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch United States 220 volt	JL255A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G PoE+ 4SFP+ Switch	JL255A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch	JL256A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
1, 3, 4, 5,10	Aruba 2930F 48G PoE+ 4SFP+ Switch PDU NA, JP or TW	JL256A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch PDU ROW	JL256A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch United States 220 volt	JL256A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ Switch	JL256A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
	Aruba 2930F 24G 4SFP Switch	JL259A
	<ul style="list-style-type: none"> 24 RJ-45 autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 24G 4SFP Switch PDU NA, JP or TW	JL259A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G 4SFP Switch PDU ROW	JL259A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G 4SFP Switch United States 220 volt	JL259A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G 4SFP Switch	JL259A#AC3

Configuration Information

1, 3,10	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
	Aruba 2930F 48G PoE+ 4SFP 740W Switch	JL557A
	<ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP 740W Switch PDU NA, JP or TW	JL557A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP 740W Switch PDU ROW	JL557A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP 740W Switch United States 220 volt	JL557A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
Rule #	Description	SKU
	Aruba 2930F 48G PoE+ 4SFP 740W Switch	JL557A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 3, 4, 5,10	Aruba 2930F 48G 4SFP Switch	JL260A
	<ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 48G 4SFP Switch PDU NA, JP or TW	JL260A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G 4SFP Switch PDU ROW	JL260A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G 4SFP Switch United States 220 volt	JL260A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G 4SFP Switch	JL260A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 3, 4, 5,10	Aruba 2930F 24G PoE+ 4SFP Switch	JL261A
	<ul style="list-style-type: none"> 24 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 24G PoE+ 4SFP Switch PDU NA, JP or TW	JL261A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G PoE+ 4SFP Switch PDU ROW	JL261A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G PoE+ 4SFP Switch United States 220 volt	JL261A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G PoE+ 4SFP Switch	JL261A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 3,10	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch	JL558A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch PDU NA, JP or TW	JL558A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	

Configuration Information

	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch PDU ROW	JL558A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch United States 220 volt	JL558A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch	JL558A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 3, 4, 5,10	Aruba 2930F 48G PoE+ 4SFP Switch	JL262A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP 1G ports min=0 \\ max=4 SFP Transceivers 1U - Height 	

Rule #	Description	SKU
	Aruba 2930F 48G PoE+ 4SFP Switch PDU NA, JP or TW	JL262A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP Switch PDU ROW	JL262A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP Switch United States 220 volt	JL262A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP Switch	JL262A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	

TAA Compliant Chassis

Rule #	Description	SKU
1, 2, 3, 4, 5, 6, 8, 9,10	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch	JL263A
	<ul style="list-style-type: none"> 24 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch PDU NA, JP or TW	JL263A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch PDU ROW	JL263A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch United States 220 volt	JL263A#B2E
	<ul style="list-style-type: none"> HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch	JL263A#AC3
	<ul style="list-style-type: none"> No Localized Power Cord Selected 	
1, 2, 3, 4, 5, 6, 8, 9,10	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch	JL559A
	<ul style="list-style-type: none"> 48 RJ-45 PoE+ autosensing 10/100/1000 ports 4 SFP/SFP+ 1G/10G ports min=0 \\ max=4 SFP/SFP+ Transceivers 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU NA, JP or TW	JL559A#B2B
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU ROW	JL559A#B2C
	<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	

Configuration Information

	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch United States 220 volt	JL559A#B2E
	<ul style="list-style-type: none"> • HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch	JL559A#AC3
	<ul style="list-style-type: none"> • No Localized Power Cord Selected 	
1, 2, 3, 4, 5, 6, 8, 9,10	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch	JL264A
	<ul style="list-style-type: none"> • 48 RJ-45 PoE+ autosensing 10/100/1000 ports • 4 SFP/SFP+ 1G/10G ports • min=0 \\ max=4 SFP/SFP+ Transceivers • 1U - Height 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch PDU NA, JP or TW	JL264A#B2B
	<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
Rule #	Description	SKU
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch PDU ROW	JL264A#B2C
	<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch United States 220 volt	JL264A#B2E
	<ul style="list-style-type: none"> • HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A) 	
	Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch	JL264A#AC3
	<ul style="list-style-type: none"> • No Localized Power Cord Selected 	
	Configuration Rules	
1	The following Transceivers install into this Switch:	
	Aruba 1G SFP LC SX 500m OM2 MMF Transceiver	J4858D
	Aruba 1G SFP LC LX 10km SMF Transceiver	J4859D
	Aruba 1G SFP LC LH 70km SMF Transceiver	J4860D
	Aruba 1G SFP RJ45 T 100m Cat5e Transceiver	J8177D
	Aruba 100M SFP LC FX 2km MMF Transceiver	J9054D
2	The following Transceivers install into this Switch:	
	Aruba 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
	Aruba 10G SFP+ LC LR 10km SMF Transceiver	J9151E
	Aruba 10G SFP+ LC ER 40km SMF Transceiver	J9153D
	Aruba 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
	Aruba 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D
3	If this switch is factory installed in HPE Racks, Then the J9583A#0D1 is required. CLIC Only - Allow the J9583AZ in all regions.	
4	Localization required on orders without #B2B, #B2C, #B2E options.	
5	If this Switch Chassis is selected for Rack Level Integration, Then the Switch Chassis needs to integrate (with #0D1) to the HPE Rack.	
6	TAA Switch Chassis are available in the US, UK, Israel, Vietnam, South Korea, India and Taiwan only.	
8	The following Transceivers install into this Switch:	
	Aruba 1G SFP LC SX 500m MMF TAA Transceiver	JL745A
	Aruba 1G SFP LC LX 10km SMF TAA Transceiver	JL746A
	Aruba 1G SFP RJ45 T 100m Cat5e TAA Transceiver	JL747A
9	The following Transceivers install into this Switch:	
	Aruba 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
	Aruba 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
10	Unbuildable/FAN required, generates CFGU: If order is quoted for India and contains "#B2C" Option, then Display the following:	

Configuration Information

For BTO shipments to India:

Please replace <Base Model>#B2C option with <Base Model>#AC3 in the Bill of Materials and add the appropriate INDIA PDU Power Cord below via Ad-Hoc:

For Factory Integration of Power Cord, please add "#0D1" to the Power Cord Sku suffix. (Ex. JL671A#0D1)

HPE 2.0m C13 to C14 PDU India Power Cord	JL671A
HPE 2.5m C15 to C14 PDU India Power Cord	JL672A
HPE 2.5m C19 to C20 PDU India Power Cord	JL673A

- Notes:**
- Drop down under power supply should offer the following options and results:
 - Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
 - Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)
 - #AC3 - No Power Cord.
 - Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

Transceivers

Remarks	Description	SKU
SFP Transceivers		
	Aruba 100M SFP LC FX 2km MMF Transceiver	J9054D
	Aruba 1G SFP LC SX 500m OM2 MMF Transceiver	J4858D
	Aruba 1G SFP LC LX 10km SMF Transceiver	J4859D
	Aruba 1G SFP LC LH 70km SMF Transceiver	J4860D
	Aruba 1G SFP RJ45 T 100m Cat5e Transceiver	J8177D
	Aruba 1G SFP LC SX 500m MMF TAA Transceiver	JL745A
	Aruba 1G SFP LC LX 10km SMF TAA Transceiver	JL746A
	Aruba 1G SFP RJ45 T 100m Cat5e TAA Transceiver	JL747A
SFP+ Transceivers		
	Aruba 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
Notes:	Temperature Limitations	
	Aruba 10G SFP+ LC LR 10km SMF Transceiver	J9151E
Notes:	Temperature Limitations	
	Aruba 10G SFP+ LC ER 40km SMF Transceiver	J9153D
Notes:	Mounting Limitations	
	Aruba 10G SFP+ LC SR 300m MMF TAA Transceiver	JL748A
	Aruba 10G SFP+ LC LR 10km SMF TAA Transceiver	JL749A
	Aruba 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
	Aruba 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D
Notes:	<ul style="list-style-type: none"> – Temperature limitations apply when the J9150D Aruba 10G SFP+ LC SR 300m OM3 MMF Transceiver or J9151E Aruba 10G SFP+ LC LR 10km SMF XCVR are configured with JL693A Aruba 2930F 12G PoE+ 2G/2SFP+ Switch. See product installation guide for more information. – Mounting limitations apply when the J9153D Aruba 10G SFP+ LC ER 40km SMF Transceiver is configured with a JL693A Aruba 2930F 12G PoE+ 2G/2SFP+ Switch. See product installation guide for more information. 	

Configuration Information

Cables

Remarks	Description	SKU
	Console Cables	
	(std 0 // max 99) User Selection (min 0 // max 99) per switch	
	Aruba X2C2 RJ45 to DB9 Console Cable	JL448A
Notes:	Option not available for Central Managed Switch Configuration; Can be ordered Separately if needed.	
	Multi-Mode Cables	
	(std 0 // max 99) User Selection (min 0 // max 99) per switch	
	HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
	HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
	HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
	HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
	HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
	HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
	HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
	HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 1m Cable	QK732A
	HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 2m Cable	QK733A
	HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 5m Cable	QK734A
	HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 15m Cable	QK735A
	HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 30m Cable	QK736A
	HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 50m Cable	QK737A
Notes:	Option not available for Central Managed Switch Configuration; Can be ordered Separately if needed.	

Switch Enclosure Options

Rule #	Description	SKU
	Mounting Kit	
	(std 0 // max 1) User Selection (min 0 // max 1) per switch	
1, 2	Aruba X414 1U Universal 4-post Rack Mount Kit	J9583B
	Configuration Rules	
1	If this Mounting Kit is order with #0D1 then it integrates to the HPE Universal Rack. (not the switch)	
2	This Rack Mount Kit is not compatible with JL258A, JL692A, and JL693A.	
	Accessories	
Notes:	For JL258A and JL692A System (std 0 // max 1) User Selection (min 0 // max 1) per switch	
	Aruba 2930F 8-port Cable Guard	JL311A
	Aruba 2930F 8-port Power Shelf	JL312A

Software

	Central	
	Cloud Services / 62XX/29XX Switch Foundation Subscriptions	
	HPE Aruba Networking Central Switch Class-2 Foundation 1 year Subscription E-STU	Q9Y73AAE
	HPE Aruba Networking Central Switch Class-2 Foundation 3 year Subscription E-STU	Q9Y74AAE
	HPE Aruba Networking Central Switch Class-2 Foundation 5 year Subscription E-STU	Q9Y75AAE
	HPE Aruba Networking Central Switch Class-2 Foundation 7 year Subscription E-STU	Q9Y76AAE
	HPE Aruba Networking Central Switch Class-2 Foundation 10 year Subscription E-STU	Q9Y77AAE
Notes:	Add the Central Cloud Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > Cloud Services	
	On-Prem Services / 62XX/29XX Switch Foundation Subscriptions	
	HPE Aruba Networking Central on Prem Switch Class-2 Foundation 1 year Subscription E-STU	R6U78AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Foundation 3 year Subscription E-STU	R6U79AAE

Configuration Information

	HPE Aruba Networking Central on Prem Switch Class-2 Foundation 5 year Subscription E-STU	R6U80AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Foundation 7 year Subscription E-STU	R6U81AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Foundation 10 year Subscription E-STU	R6U82AAE
Notes:	Add the Central On-Prem Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > On-Prem Services	
	Aruba 2930F 12G PoE+ 2G/2SFP+ Switch	JL693A
	Aruba 2930F 8G PoE+ 2SFP+ Switch	JL258A
	FedRAMP Services / 62XX/29XX Switch Foundation Subscriptions	
	Aruba Central 62xx or 29xx Switch Foundation 1 year Subscription Government E-STU	R8K94AAE
	Aruba Central 62xx or 29xx Switch Foundation 3yr Subscription Government E-STU	R8K95AAE
	Aruba Central 62xx or 29xx Switch Foundation 5 year Subscription Government E-STU	R8K96AAE
	Aruba Central 62xx or 29xx Switch Foundation 7yr Subscription Government E-STU	R8K97AAE
	Aruba Central 62xx or 29xx Switch Foundation 10yr Subscription Government E-STU	R8K98AAE
Notes:	Add the Central FedRAMP Service Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > FedRAMP	
	On-Prem Services / 62XX/29XX Switch Advanced Subscriptions	
	HPE Aruba Networking Central on Prem Switch Class-2 Advanced 1 year Subscription E-STU	R6U98AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Advanced 3 year Subscription E-STU	R6U99AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Advanced 5 year Subscription E-STU	R6V00AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Advanced 7 year Subscription E-STU	R6V01AAE
	HPE Aruba Networking Central on Prem Switch Class-2 Advanced 10 year Subscription E-STU	R6V02AAE
Notes:	Add the Central On-Prem Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > On-Prem Services	

As-a-Service

Aruba Central		
Cloud Services / 62XX/29XX Switch Foundation Subscriptions		
2	HPE Aruba Networking Central Switch Class-2 Foundation 1 year Subscription SaaS	Q9Y73AAS
2	HPE Aruba Networking Central Switch Class-2 Foundation 3 year Subscription SaaS	Q9Y74AAS
2	HPE Aruba Networking Central Switch Class-2 Foundation 5 year Subscription SaaS	Q9Y75AAS
2	HPE Aruba Networking Central Switch Class-2 Foundation 7 year Subscription SaaS	Q9Y76AAS
2	HPE Aruba Networking Central Switch Class-2 Foundation 10 year Subscription SaaS	Q9Y77AAS
Cloud Services / Switch Advanced AAS Licenses		
7	HPE Aruba Networking Central Switch Class-2 Advanced 1 year Subscription SaaS	S0W72AAS
7	HPE Aruba Networking Central Switch Class-2 Advanced 3 year Subscription SaaS	S0W73AAS
7	HPE Aruba Networking Central Switch Class-2 Advanced 5 year Subscription SaaS	S0W74AAS
7	HPE Aruba Networking Central Switch Class-2 Advanced 7 year Subscription SaaS	S0W75AAS
7	HPE Aruba Networking Central Switch Class-2 Advanced 10 year Subscription SaaS	S0W76AAS
Configuration Rules		
Rule#	Description	SKU
2	Add the Central Cloud Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > Cloud Services	
7	For IRIS reference only. No action required for OCX and Clic	

Technical Specifications

Aruba 2930F 8-port Cable Guard (JL311A)

The Cable Guard secures cables that are connected to the switch and provides extra security against theft or tampering with the switch and its cables after it is installed

Product Type	Mounting Kit
Physical characteristics	Dimensions: 1.42(w) x 4.33(d) x 0.69(h) in (3.6 x 11 x 1.75 cm) Weight: 1.28 lb (0.58 kg)
Notes	Dimensions: 10.94" x 3.62" x 1.69" or 27.8cm x 9.2cm x 4.3cm w/ears 10.94" x 1.69" x 1.69" or 27.8cm x 4.3cm x 4.3cm without ears Weight: 1.262 lbs or 57 kg (including faceplate, ears, and screws) 1.026 lbs or . 47 kg (faceplate only)
Warranty	Limited Lifetime Warranty: See http://www.hpe.com/networking/warrantysummary for warranty and support information included with your product purchase.
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

Aruba 2930F 8-port Power Shelf (JL312A)

An easy-to-use solution for attaching the external power adapter to any of the Aruba 2530 8-port switches.

Product Type	Mounting Kit
Physical characteristics	Dimensions: 10.75(w) x 6(d) x 2(h) in (27.31 x 15.24 x 5.08 cm) Weight: 0.93 lb (0.42 kg)
Overall Positioning Statement	The Aruba 2930F 8-port Power Shelf provides an easy to use solution for attaching the external power adapter to the Aruba 2930F 8G 2SFP+ PoE+ Switch. The power adapter shelf can be quickly attached on the rear of the Aruba 2930F 8G PoE+ 2SFP+ Switch and the adapter fit into place. This power adapter shelf is designed for wall, table or rack deployments.
Key Features	Quickly attach external power adapter to 8 port switch Designed for use with Aruba 2930F 8G PoE+ 2SFP+ Switch
Notes	The Aruba 2930F 8-port Power Shelf is an accessory for the Aruba 2930F 8G PoE+ 2SFP+ Switch. The shelf mounts on the back of the switch providing a place to hold the external power adapter.
Warranty	Limited Lifetime Warranty: See http://www.hpe.com/networking/warrantysummary for warranty and support information included with your product purchase.
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

Aruba 2930F 24G 4SFP+ Switch (JL253A)

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 7.88(d) x 1.73(h) in (44.25 x 20.02 x 4.39 cm) (1U height)
	Weight	5.31 lb (2.41 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
	Throughput	up to 95.2 Mpps
	Switching capacity	128 Gbps

Technical Specifications

Performance	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 49.7 dB, Pressure: 37.1 dB
	Airflow direction	Side-to-side
Electrical characteristics	Maximum heat dissipation	100.0 BTU/hr (105.5 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.6/0.4 A
	Maximum power rating	29.3 W
	Idle power	19.5 W
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
Immunity	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3

Technical Specifications

Aruba 2930F 48G 4SFP+ Switch (JL254A)		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 9.7(d) x 1.73(h) in (44.25 x 24.63 x 4.39 cm) (1U height)
	Weight	6.83 lb (3.10 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
Environment	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 54.1 dB, Pressure: 40.2 dB
	Airflow direction	Side-to-side
	Maximum heat dissipation	157.2 BTU/hr (165.8 KJ/hr)
Electrical characteristics	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.9/0.6 A
	Maximum power rating	46.6 W
	Idle power	32.7 W
	Frequency	50/60 Hz
	Notes:	
	<ul style="list-style-type: none"> Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2

Technical Specifications

Immunity	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 24G PoE+ 4SFP+ Switch (JL255A)

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	8.6 lb (3.9 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5 MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
	Throughput	up to 95.2 Mpps
	Switching capacity	128 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 54.1 dB, Pressure: 40.2 dB
	Airflow direction	Side-to-side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Silver
	Maximum heat dissipation	258.0 BTU/hr (272.2 KJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	4.9/2.4 A
	Maximum power rating	445 W
	Idle power	36.8 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
Safety	Notes:	
	<ul style="list-style-type: none"> Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Emissions	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	

Technical Specifications

Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 48G PoE+ 4SFP+ Switch (JL256A, JL256ACM)¹

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	9.83 lb (4.46 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 55.7 dB, Pressure: 41.7 dB
Environment	Airflow direction	Side-to-side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Silver
	Maximum heat dissipation	293.0 BTU/hr (309.1 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	5.1/2.5 A
	Maximum power rating	459 W
	Idle power	48.6 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz

Technical Specifications

Electrical characteristics	Notes: <ul style="list-style-type: none"> Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Notes:	¹ All hardware SKUs can be managed by Aruba Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.	

Aruba 2930F 8G PoE+ 2SFP+ Switch (JL258A, JL258ACM) ¹

I/O ports and slots	8 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	2 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	10(w) x 10(d) x 1.73(h) in (25.4 x 25.4 x 4.39 cm) (1U height)
	Weight	4.41 lb (2.0 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
Performance	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing



Technical Specifications

Environment	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 0 dB, Pressure: 0 dB Fanless
Electrical characteristics	Power efficiency certifications	DoE VI certification.
	Maximum heat dissipation	58.6 BTU/hr (61.8 kJ/hr)
	Voltage	90 - 264 VAC, rated
	Current	2.6 A
	Maximum power rating	155 W
	PoE power	125 W PoE+
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS). 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Notes:	¹ All hardware SKUs can be managed by Aruba Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.	

Technical Specifications

Aruba 2930F 8G PoE+ 2SFP+ TAA-compliant Switch (JL692A)		
I/O ports and slots	8 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	2 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	10(w) x 10(d) x 1.73(h) in (25.4 x 25.4 x 4.39 cm) (1U height)
	Weight	4.41 lb (2.0 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
Environment	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
Environment	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 0 dB, Pressure: 0 dB Fanless
	Power efficiency certifications	DoE VI certification.
Electrical characteristics	Maximum heat dissipation	58.6 BTU/hr (61.8 kJ/hr)
	Voltage	90 - 264 VAC, rated
	Current	2.6 A
	Maximum power rating	155 W
	PoE power	125 W PoE+
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS). 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11

Technical Specifications

Immunity	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Notes:	¹ All hardware SKUs can be managed by Aruba Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.	

Aruba 2930F 12G PoE+ 2G/2SFP+ Switch (JL693A)

I/O ports and slots	12 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	2 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	10 (w) x 10 (d) x 1.73 (h) in (25.4 x 25.4 x 4.39 cm) (1U height)
	Weight	4.85 lb (2.2kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 2.9 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	68 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
Environment	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 0 dB, Pressure: 0 dB Fanless
	Power efficiency certifications	meets DoE VI certification.
Electrical characteristics	Maximum heat dissipation	68.2 BTU/hr (72.0 kJ/hr)
	Voltage	90 - 264 VAC, rated
	Current	1.7 A
	Maximum power rating	170 W
	PoE power	139 W PoE+
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	

Technical Specifications

	– PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 24G 4SFP Switch (JL259A)

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 7.88(d) x 1.73(h) in (44.25 x 20.02 x 4.39 cm) (1U height)
	Weight	5.31 lb (2.41 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 49.7 dB, Pressure: 37.1 dB
Electrical characteristics	Airflow direction	Side-to-side
	Maximum heat dissipation	100.0 BTU/hr (105.5 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.6/0.4 A
	Maximum power rating	29.3 W

Technical Specifications

Electrical characteristics	Idle power	19.5 W
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 48G 4SFP Switch (JL260A)

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 9.7(d) x 1.73(h) in (44.25 x 24.63 x 4.39 cm) (1U height)
	Weight	6.83 lb (3.10 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 77.4 Mpps
	Switching capacity	104 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing

Technical Specifications

Environment	Acoustic	Power: 54.1 dB, Pressure: 40.2 dB
	Airflow direction	Side-to-side
Electrical characteristics	Maximum heat dissipation	100.0 BTU/hr (105.5 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.9/0.6 A
	Maximum power rating	46.6 W
	Idle power	32.7 W
	Frequency	50/60 Hz
Electrical characteristics	Notes: <ul style="list-style-type: none"> Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2:
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
Immunity	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 24G PoE+ 4SFP Switch (JL261A, JL261ACM) ¹

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	8.6 lb (3.9 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries

Technical Specifications

Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 54.1 dB, Pressure: 40.6 dB
	Airflow direction	Side-to-side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Silver
	Maximum heat dissipation	258.0 BTU/hr (272.2 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	4.9/2.4 A
	Maximum power rating	445 W
	Idle power	36.8 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
	Notes:	
	<ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2:
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Notes:	¹ All hardware SKUs can be managed by Aruba Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.	

Technical Specifications

Aruba 2930F 48G PoE+ 4SFP Switch (JL262A, JL262ACM) ¹		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	9.83 lb (4.46 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 77.4 Mpps
	Switching capacity	104 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
Environment	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 55.7 dB, Pressure: 41.7 dB
	Airflow direction	Side-to-side
	Power efficiency certifications	80plus.org certification: Silver
Electrical characteristics	Maximum heat dissipation	293.0 BTU/hr (309.1 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	5.1/2.5 A
	Maximum power rating	459 W
	Idle power	48.6 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8

Technical Specifications

Immunity	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Notes:	¹ All hardware SKUs can be managed by Aruba Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.	

Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch (JL263A)

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in. (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	8.6 lb (3.9 kg)
Memory and processor	Dual Core ARM® Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5 MB Ingress/7.785 MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μs (64-byte packets)
	10 Gbps Latency	< 2.9 μs (64-byte packets)
	Throughput	Up to 95.2 Mpps
	Switching capacity	128 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0°C to 40°C (32°F to 104°F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 54.1 dB, Pressure: 40.6 dB
Electrical characteristics	Airflow direction	Side-to-side
	Power efficiency certifications	80plus.org certification: Silver
	Maximum heat dissipation	258.0 BTU/hr (272.2kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	4.9/2.4 A
	Maximum power rating	445 W
	Idle power	36.8 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz

Technical Specifications

Electrical characteristics	Notes: <ul style="list-style-type: none"> Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1: 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch (JL264A)

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in. (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	9.83 lb (4.46 kg)
Memory and processor	Dual Core ARM® Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5 MB Ingress/7.785 MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μs (64-byte packets)
	10 Gbps Latency	< 2.9 μs (64-byte packets)
	Throughput	Up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768 entries
	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0°C to 40°C (32°F to 104°F) up to 10000 Feet
Environment	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)

Technical Specifications

Environment	Acoustic	Power: 55.7 dB, Pressure: 41.7 dB
	Airflow direction	Side-to-side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Silver
	Maximum heat dissipation	293.0 BTU/hr (309.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	5.1/2.5 A
	Maximum power rating	459 W
	Idle power	48.6 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1: 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
Immunity	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Aruba 2930F 48G PoE+ 4SFP 740W Switch (JL557A)

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42 (w) x 12.77 (d) x 1.73 (h) in (44.25 x 32.42 x 4.39 cm) (1U height)
	Weight	10.56 lb (4.79 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 77.4 Mpps
	Switching capacity	104 Gbps

Technical Specifications

Performance	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5,000 Feet, 0°C to 40°C (32°F to 104°F) up to 10,000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15,000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic (power and pressure) in decibels	Power: 55.1 dB, Pressure: 41.1 dB
	Airflow direction	Side to side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Gold
	Maximum heat dissipation	420.9 BTU/hr (444.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	9.2 / 4.9 A
	Maximum power rating	980W
	Idle power	49.9W
	PoE power	740 W PoE+
	Frequency	50/60 Hz
Electrical characteristics	Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Technical Specifications

Aruba 2930F 48G PoE+ 4SFP+ 740W Switch (JL558A, JL558ACM) ¹		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42 (w) x 12.77 (d) x 1.73 (h) in (44.25 x 32.42 x 4.39 cm) (1U height)
	Weight	10.56 lb (4.79 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10Gbps latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5,000 Feet, 0°C to 40°C (32°F to 104°F) up to 10,000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
Environment	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15,000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic (power and pressure) in decibels	Power: 55.1 dB, Pressure: 41.1 dB
	Airflow direction	Side to side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Gold
	Maximum heat dissipation	420.9 BTU/hr (444.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	9.2 / 4.9 A
	Maximum power rating	980W
	Idle power	49.9W
	PoE power	740 W PoE+
	Frequency	50/60 Hz
Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 		
Safety	UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	



Technical Specifications

Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	
Notes:	¹ All hardware SKUs can be managed by Aruba Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.	

Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch (JL559A)

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42 (w) x 12.77 (d) x 1.73 (h) in (44.25 x 32.42 x 4.39 cm) (1U height)
	Weight	10.56 lb (4.79 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10Gbps latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5,000 Feet, 0°C to 40°C (32°F to 104°F) up to 10,000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15,000 Feet
	Non-operating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic (power and pressure) in decibels	Power: 55.1 dB, Pressure: 41.1 dB

Technical Specifications

Environment	Airflow direction	Side to side
Electrical characteristics	Power efficiency certifications	80plus.org certification: Gold
	Maximum heat dissipation	420.9 BTU/hr (444.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	9.2 / 4.9 A
	Maximum power rating	980W
	Idle power	49.9W
	PoE power	740 W PoE+
	Frequency	50/60 Hz
	Notes: <ul style="list-style-type: none"> – Idle power is the actual power consumption of the device with no ports connected. – Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. 	
Safety	UL 60950-1: 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950- 1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825- 1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba Central; Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP	
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

Technical Specifications

Standards and Protocols

Applies to all products in series

Denial of service protection

CPU DoS Protection

Device Management

- RFC 1155 Structure and Mgmt Information (SMIv1)
- RFC 1157 SNMPv1/v2c
- RFC 1591 DNS (client)
- RFC 1901 (Community based SNMPv2)
- RFC 1901-1907 SNMPv2c, SMIv2 and Revised MIB-II
- RFC 1908 (SNMP v1/2 Coexistence)
- RFC 2576 (Coexistence between SNMP V1, V2, V3)
- RFC 2578-2580 SMIv2
- RFC 2579 (SMIv2 Text Conventions)
- RFC 2580 (SMIv2 Conformance)
- RFC 2819 (RMON groups Alarm, Event, History and Statistics only)
- RFC 3416 (SNMP Protocol Operations v2)
- RFC 3417 (SNMP Transport Mappings)
- HTML and telnet management
- HTTP, SSHv1, and Telnet
- Multiple Configuration Files
- Multiple Software Images
- SNMP v3 and RMON RFC support
- SSHv1/SSHv2 Secure Shell
- TACACS/TACACS+
- Web UI

IP Multicast

- RFC 1112 IGMP
- RFC 2236 IGMPv2
- RFC 2710 Multicast Listener Discovery (MLD) for IPv6
- RFC 3376 IGMPv3
- RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches

QoS/CoS

- IEEE 802.1p (CoS)
- RFC 2474 DiffServ Precedence, including 8 queues/port
- RFC 2475 DiffServ Architecture
- RFC 2597 DiffServ Assured Forwarding (AF)
- RFC 2598 DiffServ Expedited Forwarding (EF)
- Ingress Rate Limiting

General Protocols

- IEEE 802.1AX-2008 Link Aggregation
- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1v VLAN classification by Protocol and Port
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- IEEE 802.3ab 1000BASE-T

Technical Specifications

- IEEE 802.3ad Link Aggregation Control Protocol (LACP)
- IEEE 802.3af Power over Ethernet
- IEEE 802.3at PoE+
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.3x Flow Control
- IEEE 802.1ad Q-in-Q
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 868 Time Protocol
- RFC 951 BOOTP
- RFC 1058 RIPv1
- RFC 1256 ICMP Router Discovery Protocol (IRDP)
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1519 CIDR
- RFC 1542 BOOTP Extensions
- RFC 1918 Address Allocation for Private Internet
- RFC 2030 Simple Network Time Protocol (SNTP) v4
- RFC 2131 DHCP
- RFC 2236 IGMP Snooping
- RFC 2453 RIPv2
- RFC 2865 Remote Authentication Dial In User Service (RADIUS)
- RFC 2866 RADIUS Accounting
- RFC 3046 DHCP Relay Agent Information Option
- RFC 3411 An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks
- RFC 3412 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)
- RFC 3413 Simple Network Management Protocol (SNMP) Applications
- RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)
- RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)
- RFC 3416 Protocol Operations for SNMP
- RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP)
- RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)
- RFC 3575 IANA Considerations for RADIUS
- RFC 3576 Ext to RADIUS (CoA only)
- RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches
- RFC 4675 RADIUS VLAN & Priority
- RFC 4861 Neighbor Discovery for IP version 6 (IPv6)
- RFC 4862 IPv6 Stateless Address Autoconfiguration
- RFC 5905 Network Time Protocol Version 4: Protocol and Algorithms Specification
- UDLD (Uni-directional Link Detection)

Technical Specifications

IPv6




- RFC 1981 IPv6 Path MTU Discovery
 - RFC 2080 RIPng for IPv6
 - RFC 2081 RIPng Protocol Applicability Statement
 - RFC 2082 RIP-2 MD5
 - RFC 2460 IPv6 Specification
 - RFC 2464 Transmission of IPv6 over Ethernet Networks
 - RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 - RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
 - RFC 2925 Remote Operations MIB (Ping only)
 - RFC 3019 MLDv1 MIB
 - RFC 3315 DHCPv6 (client and relay)
 - RFC 3484 Default Address Selection for IPv6
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6
 - RFC 3810 MLDv2 for IPv6
 - RFC 4022 MIB for TCP
 - RFC 4113 MIB for UDP
 - RFC 4251 SSHv6 Architecture
 - RFC 4252 SSHv6 Authentication
 - RFC 4253 SSHv6 Transport Layer
 - RFC 4254 SSHv6 Connection
 - RFC 4291 IP Version 6 Addressing Architecture
 - RFC 4293 MIB for IP
 - RFC 4419 Key Exchange for SSH
 - RFC 4443 ICMPv6
 - RFC 4541 IGMP & MLD Snooping Switch
 - RFC 4861 IPv6 Neighbor Discovery
 - RFC 4862 IPv6 Stateless Address Auto-configuration
 - RFC 5095 Deprecation of Type 0 Routing Headers in IPv6
 - RFC 6620 FCFS SAVI
-

Summary of Changes

Date	Version History	Action	Description of Change:
20-Nov-2023	Version 28	Changed	Configuration Information section was updated. Obsolete SKUs were removed.
07-Aug-2023	Version 27	Changed	Configuration Information section was updated.
15-May-2023	Version 26	Changed	Configuration Information section was updated.
06-Feb-2023	Version 25	Changed	Configuration Information section was updated.
05-Dec-2022	Version 24	Changed	Configuration Information section was updated. Obsolete SKUs were removed and new SKUs were added.
07-Nov-2022	Version 23	Changed	Configuration Information section was updated. Obsolete SKUs were removed.
28-Jun-2021	Version 22	Changed	Standard Features and Configuration Information sections were updated. SKUs were added in Configuration Information section.
08-Mar-2021	Version 21	Changed	SKUs added in Configuration Information section.
21-Sep-2020	Version 20	Changed	Overview and Technical Specification sections were updated. New SKUs were added.
08-Sep-2020	Version 19	Changed	Configuration Information, Standard Features and Technical Specification sections were updated.
01-Jun-2020	Version 18	Changed	Standard Features and Technical Specification sections were updated.
06-Apr-2020	Version 17	Changed	Configuration Information section was updated. TAA transceivers were added, Obsolete SKUs were removed.
02-Dec-2019	Version 16	Changed	Configuration Information section was updated. Obsolete SKUs were removed.
04-Nov-2019	Version 15	Changed	Overview, Standard Features, Configuration Information and Technical Specification sections were updated.
07-Oct-2019	Version 14	Changed	Overview, Standard Features, Configuration Information and Technical Specification sections were updated.
05-Aug-2019	Version 13	Changed	Configuration Information section was updated
01-Jul-2019	Version 12	Changed	Standard Features and Technical Specification sections were updated. SKU descriptions were updated. Obsolete SKUs were removed.
04-Mar-2019	Version 11	Changed	SKU J9151D was replaced with J9151E. Obsolete SKUs were removed.
03-Dec-2018	Version 10	Changed	Software feature update: Key features, Product overview, Enhanced Capabilities and Technical Specifications updated
02-Jul-2018	Version 9	Changed	Software feature update
15-Jan-2018	Version 8	Changed	Minor changes made on Technical Specifications
08-Jan-2018	Version 7	Added	Models added: JL557A, JL558A, JL559A
03-Jul-2017	Version 6	Added	SKU added: JL448A
20-Jan-2017	Version 5	Changed	Minor changes made on Standards and protocols
07-Nov-2016	Version 4	Changed	Product overview, Features and Benefits, Technical Specifications updated
02-Sep-2016	Version 3	Changed	Product description updated.
24-Jun-2016	Version 2	Changed	Updated B2E Attribute Description for all switches on the Configuration section.
06-Jun-2016	Version 1	New	New QuickSpecs

Copyright

Make the right purchase decision.
Contact our presales specialists.



© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

c05052929 - 15576 - Worldwide - V28 - 20-November-2023